

## IP65 Vapor Tight Fixture-Tube

IP65



### SPECIFICATIONS

#### Features:


- Housing: 100% UV stabilized polycarbonate, silicon perimeter gasket, integrated stainless steel mounting brackets.
- Lens: Clear polycarbonate, UV stabilized lens that is tightly secured to the housing with polycarbonate clips.
- Knockout: 3/4" conduit is standard at either end, both end with conduit and 7/8" conduit are available.
- Gear tray: Flat heavy gauge die-formed C.R.S to attach all electrical component secured to housing by stainless steel wire.
- Reflector: Gullwing specular 320G anod aluminum reflector IS RECOMMENDED.
- Suitable for T5 and T8 configurations
- Available in one, two or three lamps model
- Available in 48 inch
- Ceiling, surface or pendant mount

#### Electrical:(Option)

- G13 G5 lampholder from BJB, AAG stucchi or others
- Terminal block, Quick disconnecter from IDEAL or WAGO
- 220-240V electronic ballast from TRIDONIC, PHILIPS, VS, OSRAM
- ADVANCE, FULHAM, GE, SYLVANIA, UNIVERSAL ballast etc
- Emergency kits or dimmable ballast, occupancy sensor
- Linear fluorescent lamp from GE, Philips, Osram etc
- CCC, CE, CB, CSA, UL cUL listed

#### Application

- Canopies
- Farmyards
- Parking Garages
- Garage & Workshops
- Cold Storage Facilities
- Food processing facilities
- Dusty & Wet Environments
- Indoor Equestrian Facility



### DIMENSIONS

| Model          | Lamp type      | Lamps     | Length | Width | Height |
|----------------|----------------|-----------|--------|-------|--------|
| MX486-Y32x3    | F32T8          | 3x32W     | 50 6/8 | 6 6/8 | 3 7/8  |
| MX486-Y32x2    | F32T8          | 2x32W     | 50 6/8 | 6 6/8 | 3 7/8  |
| MX486-Y28/54x3 | F28T5, F54T5HO | 3x28W/54W | 50 6/8 | 6 6/8 | 3 7/8  |
| MX486-Y28/54x2 | F28T5, F54T5HO | 2x28W/54W | 50 6/8 | 6 6/8 | 3 7/8  |

**NOTE:** (1) All dimensions are inches, 1 inch = 25.4 mm (2) T8 fluorescent tube US 17W = NON-US 18W, US 32W = NON-US 36W